







Schiedel ICS


Tabel met afmetingen voor asverschuivingen

	int Ø mm	80	100	130	150	180	200	230	250	300	350	400	450	500	600	700
Bocht 15°																
zie afb. rechts	A	295	295	295	295	315	315	315	334	334	-	-	-	-	-	-
	B	39	39	39	39	41	41	41	44	44	-	-	-	-	-	-
Bocht 30°																
zie afb. rechts	A	280	299	327	336	355	373	373	392	411	448	537	556	575	631	687
	B	75	80	88	90	95	100	100	105	110	120	144	149	154	169	184
Bocht 45°																
zie afb. rechts	A	307	324	341	358	376	393	427	427	461	512	594	628	662	731	799
	B	127	134	141	148	156	163	177	177	191	212	246	260	274	303	331
Bocht 85°																
zie afb. rechts	A	322	337	372	391	424	450	480	500	552	609	641	852	907	1013	1120
	B	295	309	341	359	388	412	440	458	506	558	588	781	831	928	1026
Bocht 90°																
zie afb. rechts	A	300	316	348	366	396	420	452	468	518	572	620	830	880	980	1082
	B	300	316	348	366	396	420	452	468	518	572	620	830	880	980	1082
T-stuk 45° met bocht 45°																
zie afb. rechts	A	303	330	397	405	412	456	483	497	556	625	725	785	844	963	1086
	B	345	364	444	446	455	513	515	539	592	662	773	833	892	1016	1139
Bocht 15° met buiselement																
	buiselement A	1218	1218	1218	1218	1238	1238	1238	1257	1257	-	-	-	-	-	-
	995 B	286	286	286	286	288	288	288	291	291	-	-	-	-	-	-
	buiselement A	735	735	735	735	755	755	755	774	774	-	-	-	-	-	-
	455 B	157	157	157	157	159	159	159	162	162	-	-	-	-	-	-
	buiselement A	493	493	493	493	513	513	513	532	532	-	-	-	-	-	-
	205 B	92	92	92	92	94	94	94	97	97	-	-	-	-	-	-
Bocht 30° met buiselement																
	buiselement A	1107	1126	1154	1163	1182	1200	1200	1219	1238	1275	1364	1383	1402	1458	1514
	995 B	553	558	566	568	573	578	578	583	588	598	622	627	632	647	662
	buiselement A	674	693	721	709	765	765	784	784	793	920	931	950	969	1025	1081
	455 B	303	308	316	318	323	328	328	333	338	348	372	377	382	397	412
	buiselement A	458	477	505	514	533	551	551	570	589	626	715	734	753	809	865
	205 B	178	183	191	193	198	203	203	208	213	223	247	252	257	272	287
Bocht 45° met buiselement																
	buiselement A	982	999	1016	1033	1051	1068	1102	1102	1136	1187	1269	1303	1337	1406	1474
	995 B	802	809	816	823	831	838	852	852	866	887	921	935	949	978	1006
	buiselement A	629	646	663	680	698	715	749	749	783	834	916	950	984	1053	1121
	455 B	449	456	463	470	478	485	499	499	513	534	568	582	596	625	653
	buiselement A	452	469	486	503	521	538	572	572	606	657	739	773	807	876	944
	205 B	272	279	286	293	301	308	322	322	336	357	391	405	419	448	476
Bocht 85° met buiselement																
	buisement A	405	420	455	474	507	533	563	583	635	692	724	935	990	1096	1203
	995 B	1246	1260	1292	1310	1339	1363	1391	1409	1457	1509	1539	1732	1782	1879	1977
	buisement A	362	377	412	431	464	490	520	540	592	649	681	892	947	1053	1160
	455 B	748	762	794	812	841	865	893	911	959	1011	1041	1234	1284	1381	1479
	buisement A	340	355	390	409	442	468	498	518	570	627	659	870	925	1031	1138
	205 B	499	513	545	563	592	616	644	662	710	762	792	985	1035	1132	1230
Bocht 90° met buiselement																
	buisement A	300	316	348	366	396	420	452	468	518	572	620	830	880	980	1082
	995 B	1255	1271	1303	1321	1351	1375	1407	1423	1473	1527	1575	1785	1835	1935	2037
	buisement A	300	316	348	366	396	420	452	468	518	572	620	830	880	980	1082
	455 B	755	771	803	821	851	875	907	923	973	1027	1075	1285	1335	1435	1537
	buisement A	300	316	348	366	396	420	452	468	518	572	620	830	880	980	1082
	205 B	505	521	553	571	601	625	657	673	723	777	825	1035	1085	1185	1287


Afb. Bocht 15°




Afb. Bocht 30°




Afb. Bocht 45°




Afb. Bocht 85°



Afb. Bocht 90°



Afb. T-stuk 45° met bocht 45°



Technische wijzigingen voorbehouden